

DCAM – DROP CAM

TECHNICAL SPECIFICATIONS

Operating depth 300 m

Total power consumption 30-70 watts
(100-240VAC)

ROV weight 0,4-0,8 kg

ROV dimensions 125x82 mm (125x55 mm)



DCAM	Complete set
Panoramic Dcam	Complete set
	4 color camera (horizontal) 1/3", 600 TV lines, 0.3 lux, view angle 360 °. Integrated cluster LEDs 60 (adjust light) tether 50 m (11 mm, up to 300 m) surface control/power supply unit (4 RCA video out) cable connectors set, owners manual
Panoramic Dcam	Complete set
	4 color camera (horizontal) 1/3", 600 TV lines, 0.3 lux, view angle 360 °. Integrated cluster LEDs 60 (adjust light) tether 100 m (11 mm, up to 300 m), hand reel with slip ring surface control/power supply unit 230VAC, (VGA video out) LCD monitor 15", DVR (4 - chanel HDD) cable connectors set, owners manual 2 waterproof cases integrated
Drop camera Dcam	Complete set - quantity of LEDs = 20 pcs
	color camera 1/3", 600 TV lines, 0.3 lux, view angle 90° Integrated cluster LEDs* (adjust light) tether 50 m (6 mm up to 100 m) surface control/power supply unit cable connectors set, owners manual, spare parts
Drop camera Dcam	Complete set - quantity of LEDs = 45 pcs
	color camera 1/3", 600 TV lines, 0.3 lux, view angle 90° Integrated cluster LEDs* (adjust light) tether 50 m (6 mm up to 100 m) surface control/power supply unit cable connectors set, owners manual, spare parts
Drop camera (DcamDM)	Complete set - quantity of LEDs = 20 pcs
	color camera 1/3", 600 TV lines, 0.3 lux, view angle 90° Integrated cluster LEDs* (adjust light) Depthmeter tether 100m (6 mm, up to 300 m), hand reel with slip ring surface control/power supply unit cable connectors set, owners manual, spare parts
Drop camera (DcamDM)	Complete set - quantity of LEDs = 45 pcs
	color camera 1/3", 600 TV lines, 0.3 lux, view angle 90° Integrated cluster LEDs* (adjust light) Depthmeter tether 100m (6 mm, up to 300 m), hand reel with slip ring surface control/power supply unit cable connectors set, owners manual, spare parts
Drop camera (DcamDM)	FULL Complete set - quantity of LEDs = 45 pcs
	color camera 1/3", 600 TV lines, 0.3 lux, view angle 90° Integrated cluster LEDs* (adjust light) Depthmeter , LCD monitor 15", DVR (SD) tether 100m (6 mm, up to 300 m), hand reel with slip ring surface control/power supply unit cable connectors set, owners manual, spare parts 2 waterproof cases integrated
Additional features & spare parts	
Additional equipment	Digital compass. Only Panoramatic DCAM Depth sensor. Prepared for Dcam
Tether and accessories	Hand reel k260 with sliding contact (Plastic, up to 150 m tether 4 mm)
	Hand reel k150 with sliding contact (aluminium, up to 200 m tether 4 mm)
	Hand reel k300 with sliding contact (aluminium, up to 300 m tether 6 mm)
	Tether (4mm, coaxial) per m
	Tether (7 mm, coaxial) per m
Other	Slip ring 2 wires
	Monitor LCD TFT 8"
	monitor LCD TFT 15", waterproof case integrated
	Virtual monitor (Video Glasses)
	Digital videorecorder integrated (SDHC max. 32Gb, D1 -704 x 576)
	Invertor 12V-230V, 350 W